

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
15 March 2001 (15.03.2001)

PCT

(10) International Publication Number
WO 01/19132 A1

(51) International Patent Classification⁷: H04R 3/14 (74) Agent: PHILLIPS ORMONDE & FITZPATRICK; 367 Collins Street, Melbourne, VIC 3000 (AU).

(21) International Application Number: PCT/AU00/01036

(22) International Filing Date:
1 September 2000 (01.09.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PQ 2608 3 September 1999 (03.09.1999) AU

(71) Applicant (for all designated States except US): TECH-
STREAM PTY LTD [AU/AU]; 10 Margaret Street, Box
Hill, VIC 3149 (AU).

(72) Inventor; and

(75) Inventor/Applicant (for US only): THIELE, Albert,
Neville [AU/AU]; 10 Wycombe Street, Epping, NSW 2121
(AU).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ,
DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR,
HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR,
LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ,
NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM,
TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG,
CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— With international search report.

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: IMPROVED CROSSOVER FILTERS AND METHOD



WO 01/19132 A1

(57) Abstract: An improved filter system is disclosed including a low pass filter having a response which rolls off towards a crossover frequency and a high pass filter having a complementary response which rolls off towards the crossover frequency. The responses are arranged such that the combined response of the filters is substantially constant in amplitude at least in the region of the crossover frequency. The response of the low pass filter is defined by a low pass complex transfer function having a first numerator and a first denominator. The response of the high pass filter is defined by a high pass complex transfer function having a second numerator and a second denominator. The desired response is obtained when the second denominator is substantially the same as the first denominator and the sum of the first and second numerators has substantially the same squared modulus as the first or second denominator.